



LEGEND

- Refer development permit for type of construction to be adopted.
- 150mm MIN. pavement overlap

NOTES:

1. Table Drains steeper than 5% should have erosion protection measures installed.
2. Cut batter slopes may be varied on site to ensure long term stability of batters.
3. Minimum slope of table drain inverts shall be 0.5% (1 in 200).
4. Floodways shall be constructed with cross road drainage nominated in development permit.
5. Unsealed roads shall be designed using parameters set out in AUSTRROADS "Unsealed Roads Manual" unless noted otherwise in the project drawings.
6. One access point to be constructed to each lot at a maximum slope of 1 in 6. The access point is to have a pipe crossing where a table drain is provided.
7. For pavement widths and design requirements refer Whitsunday Regional Council's Development Manual.
8. All dimensions in metres unless shown otherwise.

D	INDUSTRY STANDARD DRAWINGS WITH DEVELOPMENT MANUAL UPDATE 2018	01/08/2018
C	GENERAL UPDATES AND STANDARD REFERENCING AMENDMENTS	24/5/16
B	AREA SPECIFICATION TABLE AMENDED	10/3/98
A	ORIGINAL ISSUE	1/3/97
REVISIONS		DATE



Email: info@whitsundayrc.qld.gov.au Web: www.whitsundayrc.qld.gov.au

BOWEN
67 Herbert St
Bowen 4805 Q
Ph 07 4761 3600

COLLINSVILLE
Cnr Stanley & Conway Sts
Collinsville 4804 Q
Ph 07 4785 5366

PROSERPINE
83-85 Main St
Proserpine 4800 Q
Ph 07 4945 0200

TYPICAL CROSS SECTION
UN-KERBED ROAD

ROAD/STREET
Standard
Drawing
R-0033

A | B | C | D |